



**Efficient, easy to install, robust, long-lasting FLOODLIGHT. PREMIUM class outdoor luminaire.**

Aluminium housing, glass cover. Wide selection of optics. For illumination of various areas such as playgrounds, airports, harbours, sports fields, etc.

Made in EU



**Product name**  
EFL-B

**Light source**  
OSRAM / LUMILEDS

**Light color**  
3000 - 6500 K

**Color Rendering Index**  
Ra > 70; 80; 90

**Power**  
From 200W to 300W

**Efficacy**  
Up to 155 lm/W

**Sockets**  
Nema  
Zhaga

**Interfaces (optional)**

- one4all (DALI DT 6, DSI, switchDIM, corridorFUNCTION V2)
- ready2mains (configuration and dimming via mains)
- U6Me2 (configuration of chronoSTEP 2 via mains)

**Suitable for mains voltage peaks (burst/surge)**  
6kV / 10kV

**No noDriver**  
180 – 264VAC, 176 – 280 VDC

**Optics**  
30, 60, 90 degrees, Asymmetric

**Optical cover**  
Glass, thermally hardened

**Material**  
Heat sink: Cast aluminum, painted

**Color**  
Grey RAL 7015 or RAL7035

**Operating temperature**  
-40°C ≤ Ta ≤ +50°C

**Life expectancy L/B**  
L90 B10 by 100000 hrs (Ta = 25°C)

**Maintenance**  
Optical module sealed for life  
No internal cleaning required

**Installation**  
Adjustable bracket:  
angle -90° +90°

**Remarks**  
Luminaires are ready to install

**Size**  
370 x 488 x 78,5 mm