

## S-LINE Linear Lighting system is an energy-efficient and cost effective light solution for industrial, commercial and other indoor applications.

Made as simple as possible giving up with unnecessary components, but still with good quality of light and high lumen output. Designed to be independent luminarie for commercial applications.

Made in EU

-----Product name Material Lifetime Efficacy S-LINE Up to 165 lm/W Heat sink: aluminum extrusion, L90 B10 - 100000 h (Ta = 25°C) anodized Light color Interfaces (optional) Bracket for suspended mounting Mounting bracket: steel 2700 - 6500 K DALI, DSI, switchDIM (with memory Remarks function), corridor FUNCTION, 1-10V, Light source Optics Luminaries are ready to install DALI Device Type 6 30, 60, 90, 120 degrees, double SAMSUNG Size Integrated motion senor (optional) asymmetric, Asymmetric Right or Left **Color Rendering Index** 600 x 50 x 49 mm, Optical cover Color 900 x 50 x 49 mm, Ra > 80 PMMA White 1200 x 50 x 49 mm, Power 1500 x 50 x 49 mm, From 30W to 150W Operating temperature 2000 x 50 x 48 mm,  $-25^{\circ}C \le Ta \le +40^{\circ}C$ 3000 x 50 x 48 mm IP 20 IK 08