



SPL-G luminaires – economy class products for low budget lighting solutions.

Made in EU

A wide range of optics for small streets, bridges, pedestrian crossings, cycle paths, parks and other areas where high luminous flux is required at competitive prices. Certified to meet all modern requirements.

Power up to 50 W. Housing: High pressure die-cast aluminium, painted.

Recommended mounting height: 3–8 m.

More info on www.enimighting.com



Product name
SPL-G

Light source
LUMILEDS

Light color
2700 - 6500 K

Color Rendering Index
Ra > 70

Power
From 10W to 50W

Efficacy
Up to 152 lm/W

Suitable for mains voltage peaks (burst/surge)
6kV

Driver
180 – 264VAC

Optics
Asymmetric optics lens

Optical cover
Glass, thermally hardened

Material
Heat sink: Cast aluminum, painted

Color
Grey RAL 7015 or RAL7035

Operating temperature
-40°C ≤ Ta ≤ +40°C

Life expectancy L/B
L90 B10 by 100000 hrs (Ta = 25°C)

Maintenance
Optical module sealed for life
No internal cleaning required

Installation
Adjustable bracket:
angle -5° +15°,
Ø 60-76 mm, Ø 42-60 mm

Remarks
Luminaires are ready to install

Size
340 x 144 x 82 mm

